

MV ENDURANCE

GEARED MULTI-PURPOSE BOX SHAPED
SINGLE DECKER



GENERAL PARTICULARS

| | | | |
|--------------------------------|-------------------|-------------------------------------|---|
| BUILT | 2012 | CLASS | NKK |
| IMO | 9647318 | SUEZ CANAL (NET) | 4881.53 |
| FLAG | Antigua & Barbuda | PANAMA CANAL (NET) | 4812 |
| PORT OF REGISTRY | St. John's | IMDG / IMSBC / GRAIN FITTED? | Yes / Yes / Yes |
| CALLSIGN | V2GJ3 | MAIN ENGINE | MAK 6M32C, 2999 kW, CPP |
| DWAT (SUMMER / WINTER) | 7825 mt / 7564 mt | AUXILIARY ENGINE | 2 x MAN D28 Auxillary T-2 w. each 365 kW |
| DRAFT (SUMMER / WINTER) | 7.00 m / 6.85 m | OTHER PARTICULARS | Bowthruster with 255kW, Shaftgenerator with 360kW, Washing water tank, cement holes |
| GT / NT | 5632 / 2883 | CARGO GEAR | 2 x McGregor Cranes, SWL 30 mt, situated portside, 360 dgr, outreach min/max 4/26 m, speed hoist: 30 mt 25 m/min – 15 mt 40 m/min, luff time: 55 sec, slew spd: 1.0 rpm |
| LOA | 108.20 m | | |
| BEAM | 18.20 m | | |
| MOULDED DEPTH | 9.00 m | | |

LOADING CAPACITIES

| | | | |
|----------------------------|---|--------------------------------|--|
| NUMBER OF HOLDS | 3 | REEFER | N/A |
| TYPE OF HOLD(S) | No 2 box shaped, No 1 and 3 narrowing | CAPACITY (GRAIN / BALE) | No.1: 2772.0 cbm No.2: 3903.1 cbm No.3: 3616.4 cbm Total 10291.5 cbm |
| TPC | 17.87 mt/cm | HATCH OPENINGS | No.1: 17.5 x 15.2 m No.2: 25.9 x 15.2 m No.3: 25.2 x 15.2 m |
| HATCHCOVER TYPE | hydraulic folding type | HOLDS | No.1: 18.9 x 15.2 / 6.0 x 11.2 m No.2: 29.4 x 15.2 x 9.25 m No.3: 25.2 x 15.2 / 7.7 x 9.25 m |
| HATCHCOVER STRENGTH | No.1: 2.2 mt/sqm, No.2,3: 2.5 mt/sqm | | |
| TWEENDECK STRENGTH | N/A | | |
| TANKTOP STRENGTH | 15.0 mt/sqm | | |
| HOLD VENTILATION | mechanical / 6 airchanges per hour (empty hold) | | |
| CONTAINERS | N/A | | |

SPEED AND CONSUMPTION

| | |
|-----------------------------|---|
| AT SEA | abt 11.5 / 11.0 kn on abt 11mt IFO 380, no MGO (max 0,5% S) |
| IN PORT WITHOUT GEAR | abt 1 mt MGO |
| IN PORT WITH GEAR | abt 2 mt MGO |
| FUEL OIL CAPACITY | total 407,7 cbm |
| DIESEL OIL CAPACITY | total 134,9 cbm |

Bunker specifications to be in accordance with ISO fuel standard 8217: 2010 or later versions, **with max 0,5% Sulphur content.**
Fuel: IFO 380 RMG
MGO: DMA

BUNKERS

Speed and consumption figures are based on good weather conditions upto BF 3 and Douglas sea state 3 with no adverse current and no negative influence of swell, trim and water temperatures.

Fuel/MGO must be proven stable and homogenous, not to contain chemical waste and/or used marine and/or automotive lubricants, comply with MARPOL ANNEX VI requirements in force since May 19th 2005 including all further SECA's **and including the 0.50% Sulphur limit applicable as of 01 January 2020**, comply with EU directive 1999/327EC as amended Bunkering is always subject to Master's approval and fuels of different supplier/port/grade always to be separated by vessel's tanks.

INSURANCE

| | |
|------------------------|------------------------------|
| P&I CLUB | P&I CLUB Gard |
| H&M INSURER | Georg Duncker GmbH & Co. KG |
| OWNERS | MS "Endurance" GmbH & Co. KG |

The fuel shall be homogeneous blends of hydrocarbons derived from petroleum refining. The fuel shall be free from inorganic acids and used lubricating oils. The fuel should not include any added substance or chemical waste which jeopardizes the safety of the plant, or adversely affects the performance of the machinery, or is harmful to personnel, or contributes overall to additional air pollution.

The vessel to have liberty of using MGO for generators when entering/leaving port, maneuvering in shallow/narrow waters, canals, rivers and at other limited occasions, also if the shaft generator cannot be used due to bad weather.